

Bestelformulier

E-mail: bestelling@camlog.nl



















Fax: +31 (0)348 820 011

| | |
|-------------|---------------------|
| Afzender | |
| Klantnummer | Datum, handtekening |

F2022-1411nl

CAMLOG®

Prosthetics (Vario SR)

| | | | Ø 3,8 | | Ø 4,3 | | Ø 5,0 | | Ø 6,0 | |
|---|------------|-----------------|-------|------------|-------|------------|-------|------------|-------|------------|
| | | | Aant. | Artikel | Aant. | Artikel | Aant. | Artikel | Aant. | Artikel |
| CAMLOG® Vario SR abutment (straight, 20° angled, 30° angled) | | | | | | | | | | |
|  | | straight | | K2560.3808 | | K2560.4308 | | K2560.5008 | | K2560.6008 |
|  | | 20° angled | | K2561.3800 | | K2561.4300 | | K2561.5000 | | K2561.6000 |
|  | | 30° angled | | K2562.3800 | | K2562.4300 | | K2562.5000 | | K2562.6000 |
| CAMLOG® Vario SR aligning tool (20° angled, 30° angled), protection cap | | | | | | | | | | |
|  | | 20° angled | | J2569.0001 | | J2569.0001 | | J2569.0001 | | J2569.0001 |
|  | | 30° angled | | J2569.0002 | | J2569.0002 | | J2569.0002 | | J2569.0002 |
|  | | | | J2568.4300 | | J2568.4300 | | J2568.6000 | | J2568.6000 |
| CAMLOG® Vario SR impression cap (open tray, closed tray), analog | | | | | | | | | | |
|  | | open tray | | J2566.4300 | | J2566.4300 | | J2566.6000 | | J2566.6000 |
|  | | closed tray | | J2565.4300 | | J2565.4300 | | J2565.6000 | | J2565.6000 |
|  | | | | J2567.4300 | | J2567.4300 | | J2567.6000 | | J2567.6000 |
| CAMLOG® Vario SR coping, Titanium cap, base for bar (laser-weldable), prosthetic screw | | | | | | | | | | |
|  | POM | crown, straight | | J2563.4302 | | J2563.4302 | | J2563.6002 | | J2563.6002 |
|  | POM | crown, angled | | J2563.4303 | | J2563.4303 | | J2563.6003 | | J2563.6003 |
|  | POM | bridge | | J2563.4301 | | J2563.4301 | | J2563.6001 | | J2563.6001 |
|  | Ti alloy | bridge | | J2564.4301 | | J2564.4301 | | J2564.6001 | | J2564.6001 |
|  | Ti Grade 4 | bar | | J2570.4300 | | J2570.4300 | | J2570.6000 | | J2570.6000 |
|  | | | | J4005.2004 | | J4005.2004 | | J4005.2004 | | J4005.2004 |
| CAMLOG® Lab analog, lab screw, Vario SR lab screw | | | | | | | | | | |
|  | | | | K3010.3800 | | K3010.4300 | | K3010.5000 | | K3010.6000 |
|  | | angled | | J4006.1601 | | J4006.1601 | | J4006.2001 | | J4006.2001 |
|  | | straight | | J4008.1600 | | J4008.1600 | | J4008.2000 | | J4008.2000 |

Hartelijk dank voor uw bestelling!

Volgens onze algemene leveringsvoorwaarden. Heeft u nog vragen? Bel customer service: +31 (0)348 820 010.

a perfect fit™